

Figure 1




Figure 2




Figure 3




Figure 4






Figure 5



6 / 23


Figure 6



7 / 23

Figure 7

Metals Extraction VS Residence Time for Hydrofoil Impeller




x Pb
△ Ca
▲ Cr
▽ Zn



8 / 23

Figure 8

Variation of Zeta Potential, pH and Conductivity VS Concentration of Sodium Metaphosphate for a Partly Washed Dust Slurry




p.z.c – point zero charge (isoelectric point)



9 / 23

Figure 9

Metals Extraction VS Residence Time for High Shear Impeller



X Pb
△ Ca
△ Cr
▽ Zn

10 / 23

MATRIX C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.65	gm/cm/s
SOUND SPEED	149658.57	m/s
pH	11.24	
PERCENT SOLIDS,VOLUME	0.58	

SOLVENT 

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	625.75	$\mu S / Cm$
TEMPERATURE	24.28	DEG. C
FIXED LOSS	7.19	dB
DENSITY	1.10	gm / Cm ³




FIG. 10A

SAMPLE ATTN. _____
SOLVENT ATTN. - - - - -

11 / 23

MATRIX ☐C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.65	gm/cm/s
SOUND SPEED	149658.57	m/s
pH	11.24	
PERCENT SOLIDS,VOLUME	0.58	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	625.75	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.28	DEG. C
FIXED LOSS	7.19	dB
DENSITY	1.10	gm / Cm ³




FIG. 10B

SUBSTITUTE SHEET (RULE 26)

12 / 23

MATRIX ☐

C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN-WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.65	gm/cm/s
SOUND SPEED	149658.57	m/s
pH	11.24	
PERCENT SOLIDS, VOLUME	0.58	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	625.75	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.28	DEG. C
FIXED LOSS	7.19	dB
DENSITY	1.10	gm / Cm ³




FIG. 10C

DIFF. PDS (AREA) ———
CUMULATIVE (AREA) - - - - -

13 / 23

MATRIX ☐

C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES \ IRON OXIDE IN WATER TO
30 um. MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.65	gm / cm / s
SOUND SPEED	149658.57	m / s
pH	11.24	
PERCENT SOLIDS, VOLUME	0.58	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\ WATER

CONDUCTIVITY	625.75	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.28	DEG. C
FIXED LOSS	7.19	dB
DENSITY	1.10	gm / Cm ³




FIG. 10D

14 / 23

MATRIX ☐C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES \ IRON OXIDE IN WATER TO
30 um. MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm/cm/s
SOUND SPEED	148998.63	m/s
pH	11.33	
PERCENT SOLIDS, VOLUME	0.69	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	701.44	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.44	DEG. C
FIXED LOSS	7.20	dB
DENSITY	1.18	gm / Cm ³





FIG. 11A


SAMPLE ATTEN. _____
 SOLVENT ATTEN. - - - - -

15 / 23

MATRIX 

C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm/cm/s
SOUND SPEED	148998.63	m/s
pH	11.33	
PERCENT SOLIDS, VOLUME	0.69	

SOLVENT 

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	701.44	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.44	DEG. C
FIXED LOSS	7.20	dB
DENSITY	1.18	gm / Cm ³





FIG: 11B

16 / 23

MATRIX 

C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES \ IRON OXIDE IN WATER TO
30 um. MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm/cm/s
SOUND SPEED	148998.63	m/s
pH	11.33	
PERCENT SOLIDS, VOLUME	0.69	

SOLVENT 

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	701.44	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.44	DEG. C
FIXED LOSS	7.20	dB
DENSITY	1.18	gm / Cm ³




FIG. 11C

17 / 23

MATRIX ☐

C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES \ IRON OXIDE IN WATER TO
30 um. MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm / cm / s
SOUND SPEED	148998.63	m / s
pH	11.33	
PERCENT SOLIDS, VOLUME	0.69	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\ WATER

CONDUCTIVITY	701.44	$\mu\text{S} / \text{Cm}$
TEMPERATURE	24.44	DEG. C
FIXED LOSS	7.20	dB
DENSITY	1.18	gm / Cm ³




FIG. 11D

DIFF. PDS (NUM.) —————
CUMULATIVE (NUM.) - - - - -

18 / 23

MATRIX C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICES \IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4 . 4	
ACOUSTIC IMPEDANCE	1 . 75	gm /cm /s
SOUND SPEED	148658 .25	m /s
pH	11 . 26	
PERCENT SOLIDS,VOLUME	1 . 54	

SOLVENT 

C:\ACOUSTIC PARTICLE SIZER\CAL\ WATER

CONDUCTIVITY	748 . 67	$\mu\text{S} / \text{Cm}$
TEMPERATURE	22 . 68	DEG. C
FIXED LOSS	7 . 17	dB
DENSITY	1 . 18	gm / Cm ³




FIG. 12A

SAMPLE ATTN. —————
SOLVENT ATTN. - - - - -

19 / 23

MATRIX ☐C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm/cm/s
SOUND SPEED	148658.25	m/s
pH	11.26	
PERCENT SOLIDS, VOLUME	1.54	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	748.67	$\mu\text{S} / \text{Cm}$
TEMPERATURE	22.68	DEG. C
FIXED LOSS	7.17	dB
DENSITY	1.18	gm / Cm3




FIG. 12B

20 / 23

MATRIX ☐C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm/cm/s
SOUND SPEED	148658.25	m/s
pH	11.26	
PERCENT SOLIDS, VOLUME	1.54	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	748.67	$\mu\text{S} / \text{Cm}$
TEMPERATURE	22.68	DEG. C
FIXED LOSS	7.17	dB
DENSITY	1.18	gm / Cm ³




FIG. 12C

21 / 23

MATRIX ☐C:\ACOUSTIC PARTICLE SIZER\APS-
MATRICIES\IRON OXIDE IN WATER TO
30 um.MAT

VERSION	4.4	
ACOUSTIC IMPEDANCE	1.75	gm/cm/s
SOUND SPEED	148658.25	m/s
pH	11.26	
PERCENT SOLIDS, VOLUME	1.54	

SOLVENT ☐

C:\ACOUSTIC PARTICLE SIZER\CAL\WATER

CONDUCTIVITY	748.67	$\mu\text{S}/\text{Cm}$
TEMPERATURE	22.68	DEG. C
FIXED LOSS	7.17	dB
DENSITY	1.18	gm/Cm ³




FIG. 12D

SUBSTITUTE SHEET (RULE 26)




FIG. 13




FIG. 14